CONDUCTIVE POLYMER ALUMINUM SOLID ELECTROLYTIC CAPACITORS

HMR Series

CHIP TYPE,125℃ HIGH TEMPERATURE



Operating with wide temperature range -55~+125°C
Low ESR, high ripple current
Endurance 2000 hours
RoHS & REACH compliant, Halogen-free

SPECIFICATIONS

Items	Characteristics
Operation Temperature Range	-55 ~ +125°C
Voltage Range	16 ~ 50V
Capacitance Range	22 ~ 1000μF
Capacitance Tolerance	±20% at 120Hz, 20°C
Leakage Current	≤Specified value (after 2 minutes application of rated voltage at 20°C).
Dissipation Factor (tan δ)	≤Specified value at 120Hz, 20°C.
ESR (*2)	≤Specified value at 100KHz, 20°C.
Stability at Low Temperature	Measurement frequency : 100KHz Impedance Ratio ZT/Z20 (max.): Z(+125°C)/Z(20°C) ≤1.15; Z(-55°C)/Z(20°C) ≤1.25
Damp Heat (Steady State)	When the capacitors are restored to 20°C after the rated voltage is applied for 1000 hours at 60°C, 90% RH, they meet the characteristics listed below. Capacitance Change: Within ±20% of initial value Dissipation Factor: 150% or less of initial specified value ESR (*2): 150% or less of initial specified value Leakage Current: Initial specified value or less
Endurance	When the capacitors are restored to 20°C after 2000 hours application of the rated voltage at 125°C, they meet the characteristics listed below. Capacitance Change: Within ±20% of initial value Dissipation Factor: 150% or less of initial specified value ESR (*2): 150% or less of initial specified value Leakage Current: Initial specified value or less
Resistance to Soldering Heat	After reflow soldering and restored at room temperature, they meet the characteristics listed below. Capacitance Change: Within ±10% of initial value Dissipation Factor: 130% or less of initial specified value ESR (*2): 130% or less of initial specified value Leakage Current: Initial specified value or less
Marking	Red print on the case top.

(*1) If any doubt arises, measure the leakage current after the voltage treatment of applying DC rated voltage continuously to the capacitor for 120 minutes at 105°C.
(*2) Should be measured at both of the terminal ends closest where the terminals protrude through the plastic platform.
(*3) The value before test of examination of resistance to soldering.

DRAWING (Unit: mm)



*1. Applicable to ∅5~∅8
*2. Applicable to ∅10 and above